

Socket Fusion Tool Kit

Includes:

- Hot Head Tool
- Nozzle Regulator
- Heater Muff
- Fusion Face
- Depth Gauge
- Cold Ring

Hot Head Gas Fired Tool		
Product Number	Used With Pipe Sizes (in)	Item Description
FTK010	1	Hot Head Gas Fired Tool Kit
FTK012	1-1/4	
FTK015	1-1/2	
FTK020	2	

Socket Fusion Tools



• The hot head gas fired tool fits 2” fittings and requires fusion faces for smaller sizes.

• Use a gas torch to heat the hot head until the thermometer reads 550°F. Then remove the torch to allow the heat to “soak”. Do not exceed 600°F.

• After using the hot head, place it into the insulated heater muff to help maintain its heat and also for protection during storage.

Hot Head Gas Fired Tool			
Product Number	Item Description	Used With Pipe Sizes (in)	Approx. Wt. (lbs)
HHT	Hot Head Gas Fired Tool	1 to 2	3.5



Nozzle Regulator		
Product Number	Item Description	Approx. Wt. (lbs)
NR	Nozzle Regulator	1

Insulated Heater Muff		
Product Number	Item Description	Approx. Wt. (lbs)
HM	Heater Muff	2.5



Fusion Faces		
Product Number	Pipe Size (in)	Approx. Wt. (lbs)
FF010	1	.5
FF012	1-1/4	.6
FF015	1-1/2	.8
FF020	2	.9

Cold Rings		
Product Number	Pipe Size (in)	Approx. Wt. (lbs)
CR010	1"	1
CR012	1-1/4"	1.5
CR015	1-1/2"	2
CR020	2"	2.25

Depth Gauges		
Product Number	Pipe Size (in)	Approx. Wt. (lbs)
DG010	1"	.13
DG012	1-1/4"	.21
DG015	1-1/2"	.16
DG020	2"	.34