

**Spears PVC Lab-cock Valves**

SPEARS PVC LABCOCK VALVE		
Product Number	IPS Size (in)	Box Qty.
LABCOCK	1/4	25

- Threaded valve ends w/ male & insert adapters.
- Maximum Service Temperature: 140°F.
- Pressure Rating @ 73°F, Water: 150 PSI.
- Includes O-rings and Hex Wrench for quick assembly of adapters with valve.



**PVC Butterfly Valves**



- PVC body with PVDF disc.
- Stainless steel shaft (non-wetted part).
- Wafer style (for ANSI, full face, flat flanges)
- 150 PSI pressure rated from -5° F to 140°F.

Spears® PVC Butterfly Valves		
Product Number	IPS Size (in)	Approx. Wt. (lbs)
SBV020	2"	5.0
SBV030	3"	5.0
SBV040	4"	7.0
SBV060	6"	11.0
SBV080	8"	16.0

**Cast Iron Butterfly Valves (Imported)**

Cast Iron Butterfly Valves		
Product Number	IPS Size (in)	Approx. Wt. (lbs)
BFV030	3"	10
BFV040	4"	12
BFV060	6"	18
BFV080	8"	33

- Designed for Swimming Pools, Irrigation Systems and Water Systems.
- Spring loaded lever lock handles (included).
- Notched throttling plate allows balancing in 10° increments.
- Positive bubble-tight shutoff to 150 PSI.
- Corrosion resistant: ductile iron with nickel chrome plated disc.
- Stainless steel type 304 stem.
- EPDM seat.



**Simmons Frost-Proof Yard Hydrant (Domestic)**

Hydrant is fully frost -proof. Free flow is assured even in sub-zero weather because the shutoff valve is below the frost line. The hydrant automatically drains through a drain port when shutoff to prevent freezing.

Simmons Frost-Proof Hydrants (Domestic)				
Product Number	Simmons Model	Bury Depth (ft)	Pipe Length (in)	Approx. Wt. (lbs)
YH1	4800	1	33	11.5
YH2	4802	2	47	14.5
YH3	4803	3	59	17



**RELIABLE:** Assures running water when temperature is below freezing.

**SAFE:** Draining below frost line when shut off.

**SECURE:** May be padlocked when not in use.