

Spears True Union Ball Check Valves, PVC & CPVC

- Available in PVC or CPVC with EPDM or Viton® O-rings.
- 1/2" - 2" Sizes provided with both threaded and slip connections.
- Unique positive shut off design with minimum back pressure.
- Maximum Internal Pressure rating @ 73°F 1/2" - 2" 235 PSI.
- Excellent chemical and corrosion resistance for a wider variety of applications.



Spears True Union Ball Check Valves, PVC & CPVC								
IPS Size (in)	PVC				CPVC			
	Product Number	Spears Number	O-Ring Material	Approx. Wt. (lbs)	Product Number	Spears Number	O-Ring Material	Approx. Wt. (lbs)
1/2	TUCV005	2229-005	EPDM	.72	TUCV005C	2229-005C	Viton	.77
3/4	TUCV007	2229-007	EPDM	1.18	TUCV007C	2229-007C	Viton	1.24
1	TUCV010	2229-010	EPDM	1.59	TUCV010C	2229-010C	Viton	1.69
1-1/4	TUCV012	2229-012	EPDM	2.01	TUCV012C	2229-012C	Viton	2.14
1-1/2	TUCV015	2229-015	EPDM	3.16	TUCV015C	2229-015C	Viton	3.34
2	TUCV020	2229-020	EPDM	4.85	TUCV020C	2229-020C	Viton	5.12

Flo Control™ Spring Loaded Check Valves, PVC



- Slip or threaded connection.
- Spring poppet type design.
- Buna-N seat seal.
- 200 PSI maximum working pressure @ 72°F/

Flo Control® Spring Loaded Check Valves					
Slip Product Number	Threaded Product Number	IPS Size (in)	Body Length (in)	Approx. Weight (lbs)	Box Qty.
101105	100105	1/2	4-1/8	4.0	20
101107	100107	3/4	4-1/8	4.5	20
101110	100110	1	5-1/4	8.5	20
101112	100112	1-1/4	6-3/16	12.0	15
101115	100115	1-1/2	6-3/16	12.5	15
101120	100120	2	7	14.0	10

Flo Control™ Swing Check Valves, PVC



- Style 1500 Check Valve
- Compression Connection

- Style 1520 Check Valve
- Slip (Glued) Connection

- Flapper Design
- Designed for low pressure and sewage applications

Flo Control PVC Swing Check Valves					
Product Number	IPS Size (in)	Connection Style	Length (in)	Box Qty.	Approx. Wt. (lbs)
150012	1-1/4	Compression	7-1/2	5	1.12
150015	1-1/2	Compression	7-1/2	5	1.24
150020	2	Compression	9-3/4	8	1.93
150030	3	Compression	14	2	5
152030	3	Slip	9	4	2.5
152040	4	Slip	9-1/2	1	3.2