

**Midland Float Valves**

- Midland float valves are made of brass throughout.
- The lid, or cover, is furnished with a tapering guide to direct it to a perfect seating when the valve is closed.
- By removing the two brass bolts and connecting the handle in position perpendicular to that shown, the valve can be used on the side of the watering trough, instead of the bottom.



Midland Float Valves				
Product Number	NPT Size (in)	Approx. Wt. (lbs)	Replacement Parts	
			Handle	Washer
MFV007	3/4"	1	MFVH007	MFVW007
MFV010	1"	2	MFVH010	MFVW010
MFV012	1-1/4"	2	MFVH012	MFVW012
MFV015	1-1/2"	3	MFVH015	MFVW015
MFV020	2"	4	MFVH020	MFVW020

**Reliable Floats**

The Reliable Float will operate both high and low pressure cut-off valves for **MANY YEARS** without losing its buoyancy. It can withstand subfreezing winter conditions, the searing heat of summer, and extraordinary physical abuse. It can even be perforated and still perform its task!



Reliable Floats			
Product Number	Float Diameter (in)	Float Thickness (in)	Approx. Wt. (lbs)
10RFP	10	3.5	.6
12RFP	12	3.5	.8

**Reliable Float Tie Rods & Clamps**

Float Tie Rods & Clamps		
Product Number	Item Description	Approx. Wt. (lbs)
RFTR	9" Float Tie Rod	.1
RFTRC	Float Tie Rod Clamp	.1



**Livestock Watering Valves**

- Turns every stock tank, trough, barrel, or pan into an automatic waterer.
- Sturdy, adjustable brackets tighten down with thumb screws and make installation on edges of tanks and troughs fast and easy.
- Accepts standard 3/4" garden hose thread. Direct pipe installation quickly achieved with 3/4" adapter.
- One piece plastic float molded from durable, maintenance free polyethylene.
- Reversible, neoprene valve seat delivers long life.
- Longer float leverages up to 70 lbs water pressure with 300 gallons per hour capacity.



Livestock Watering Valves		
Product Number	Connection Size (in)	Approx. Wt. (lbs)
R825	3/4 FNPT	1.67