

1-1/2" Heavy Duty Filter Housings

1½" NPT American Plumber Heavy Duty Housings							
Product Number	Model Number	Sump Color	Cap Color	Inlet/Outlet (in)	Overall Dimensions (in)	Operating Pressure (PSI)	Operating Temperature (F°)
W15	W15-PR	Gray	Black	1½" NPT	13-5/8" x 7¼"	30-100	40-100°F
W2015	W2015-PR	Gray	Black	1½" NPT	23-7/8" x 7¼"	30-100	40-100°F

The large body size of the W15 and W2015 filter housings allows for extra large cartridge capacity and higher flow rates. Ideal for use on spas, hot tubs, trickle irrigation, farm uses, and many other commercial and industrial applications.

- Large capacity housing designed for whole house and high-flow applications.
- Equipped with pressure relief button on the inlet side of the cap.
- Completely Rust-Resistant
- Easy To Install
- Housing meets the Water Conditioning Foundation standards of 240 psi hydrostatic leaks test and 400 psi minimum ultimate burst pressure based on the rated operating pressure of 100 psi.
- Accepts large capacity 4-1/2" diameter cartridges. (See page C-4).
- Stainless Steel Mounting Bracket kits available. (Optional---See page C-3).
- Housing Construction: Polypropylene Sump, Glass-Filled ABS Filter Head, Buna-N O-ring.
- Recommended Maximum Operating Pressure: 100 PSI.
- Recommended Maximum Operating Temperature: 100°F.

