

Taste & Odor Filter Cartridge for 1-1/2" Housings

Granular Activated Carbon Cartridges for 1-1/2" Housings					
Product Number	Model Number	Gallons Per Minute	Overall Dimensions (in.)	Qty. Master Pack	Qty Per Package
GACBB10	GAC-BB10	3	9¾" x 4-1/2"	12/ea	1

GAC-BB10 Granular Activated Carbon Cartridge

Type: Granular Activated Carbon

Materials:

- Polystyrene End Caps
- Polystyrene Outer Casing
- Spun Polypropylene Post Filter
- Polyester Expansion Pad
- Buna-N Gaskets

Flow Rate: 3 GPM

Temp: 40°F to 125°F
(4.4°C to 74°C)



The GAC Cartridges contain Bituminous coal-based activated carbon which is highly effective at reducing certain organic chemicals, such as EDB, TCE, PCBs, and THMs in addition to removing chlorine. A nominal 20 micron post filter is incorporated to reduce carbon fines and other suspended particles. Cartridges are engineered to allow water to enter the bottom and filter through the entire bed of carbon before exiting through the top, ensuring maximum adsorption.

Taste & Odor Cartridge (High Flow Rate) for 1-1/2" Housings

Radial Flow Carbon Cartridge for 1-1/2" Housings					
Product Number	Model Number	Gallons Per Minute	Overall Dimensions (in.)	Qty. Master Pack	Qty Per Package
WRC25HD	WRC25HD	15	9¾" x 4-1/2"	4 ea	1

WRC25HD Radial Flow Carbon Cartridge

Type: Radial Carbon

Materials:

- Granular Activated Carbon with Polypropylene Media
- Polyethylene Outer Casing
- Polypropylene Core
- Buna-N Gaskets

Flow Rate: 15 GPM

Temp: 40°F to 145°F
(4.4°C to 74°C)



Ideal for POE (whole house) and other high flow rate applications. Unique design and nominal 25-micron inner wrap reduces carbon fines. Effectively reduces bad taste, odor, and chlorine taste & odor from water. Recommended for whole house taste and odor filtration. Fits 1-1/2" heavy duty housings.