

Reverse Osmosis Systems

American Plumber WRO-3500 Reverse Osmosis System								
Product Number	Model Number	System Capacity (gpd)	Tank Capacity (gal)	Membrane Type	Tank Diameter (in)	Tank Height (in)	Operating Temperature (F°)	Pressure Range (PSI)
ARO	WRO-3500	7.6	3.2	TFC	11.3	16.75	40-100°F	40-100



- Feed Water pH limits: 4-11
- Maximum Hardness: 10 gpg **
- Iron, Sulfide, & Manganese limit: < .01 ppm
- Total Dissolved Solids limit < 1500 ppm
- Chlorinated Water limit: < 2 ppm

* Feed water that is below the minimum pressure requires a booster pump before the R.O.

**Feed water that exceeds the maximum hardness requires a softener before the R.O.

Replacemet Cartridges for ARO (WRO-3500)	
R.O. Membrane (TFC)	Cartridge Replacement Set
AROM	WROR

- NSF-Certified contaminant reduction!
- Reduces Cryptosporidium & Giardia cysts, lead, dissolved minerals, certain salts, bad taste & odor, and chlorine taste and odor.
- Reduces Nitrate/Nitrite, Cadmium, Chromium (Hexavalent and Trivalent), Barium, and Radium 226/228.
- Plus, reduces Arsenic V. (Must only be used for arsenic reduction on chlorinated water supplies containing detectable residual free chlorine at the system inlet. Water systems using an in-line chlorinator should provide a one-minute chlorine contact time before the R.O. system).
- Includes all items for standard installation and operation: filter cartridges, R.O. membrane, Lead-free, long-reach faucet, and installation hardware.
- Designed for chlorinated & non-chlorinated water supplies.
- Has an electronic water quality monitor which tells you when the membrane needs to be changed. No more guessing!
- The American Plumber WRO-3500 is a Consumers Digest Best Buy!