

Unitra Self-Priming Pumps

Features:

- Self-Priming Design
- Cast Iron Case
- Close Coupled 3500 RPM, ODP Motor



**LSP 3/4 to 2 HP
Molded Impellers
Top Suction**



**LSP 3 & 5 HP
Brass Impellers
Flapper Suction Valve**

Unitra LSP Series Pumps							
Product Number	Depth to Water (ft)	Capacity In GPM					Shut Off Pressure PSI
		@ Discharge Pressure					
		20 PSI	30 PSI	40 PSI	50 PSI	60 PSI	
LSP071	5	41	35	16			43
	15	37	24	-			39
LSP101	5	50	40	27			51
	15	46	34	20			46
LSP151	5	58	49	39			46
	15	51	40	14			42
LSP201	5	67	61	48			53
	15	57	52	39			49
LSP301MH	5	156	124	84			43
	15	140	108	40			38
LSP301HH	5	123	108	87	60		56
	15	108	98	76	44		51
LSP501MH	5	218	190	160	118		61
	15	206	176	140	90		57
LSP501HH	5	162	160	146	118	80	69
	15	151	150	136	104	54	64

Performance at sea level.

Unitra LSP Series Self-Prime Pumps						
Product Number	HP	Voltage	Phase	Suction (FNPT)	Discharge (FNPT)	Approx. Wt. (lbs)
LSP071	3/4	115/230	1	1-1/2	1-1/2	65
LSP101	1	115/230	1	1-1/2	1-1/2	69
LSP151	1-1/2	230	1	1-1/2	1-1/2	69
LSP201	2	230	1	1-1/2	1-1/2	95
LSP301MH	3	230	1	2-1/2	1-1/2	144
LSP301HH	3	230	1	2-1/2	2	144
LSP501MH	5	230	1	3	2-1/2	182
LSP501HH	5	230	1	2-1/2	2	182

Three phase motors available as special order.