

**Myers S-33 Sump Pump**

**Features and Benefits**

- Designed for drain water removal or permanent applications with small amounts of debris
- Wide-angle or vertical mechanical switch for small 10-1/2" diameter sumps
- Oil-filled PSC motor for maximum heat dissipation, continuous bearing lubrication
- Recessed vortex impeller for free flow of liquids and solids
- Thermal overload protection with automatic reset
- Dual ball-bearing motor and additional lip seal provide durability and longer pump life
- Durable PSC motor for years of service



Myers S-33 Sump Pump Performance												
<b>Head</b>	2'	4'	6'	8'	10'	12'	14'	16'	18'	20'	22'	
<b>GPM</b>	32	32	32	31	29	27	25	22	20	15	10	

Myers S-33 Sump Pump							
Product Number	Discharge Size (FNPT)	Maximum Solids (in)	HP	Voltage	Cord Length (ft)	Control	Approx. Wt. (lbs)
S33A1	1-1/2	1/4	1/3	115	10	Ball Float	21

**Myers SSM33 Sump Pump**

**Features and Benefits**

- Removal of drainage water and light septic tank effluent
- Automatic and manual operation models available
- Piggyback wide-angle or vertical mechanical switch
- Oil-filled motor for maximum heat dissipation, continuous bearing lubrication
- Recessed vortex impeller for free flow of liquids and solids
- Thermal overload protection with automatic reset



Myers SSM33 Sump Pump												
<b>HEAD (FT)</b>	2'	4'	6'	8'	10'	12'	14'	16'	18'	20'	22'	
<b>GPM</b>	31	30.5	30.2	29.7	29	27.5	26	23.5	20	12	4	

Myers SSM-33 Sump Pump							
Product Number	Discharge Size (FNPT)	Maximum Solids (in)	HP	Voltage	Cord Length (ft)	Control	Approx. Wt. (lbs)
SSM33PC1	1-1/2	1/2	1/3	115	10	Ball Float	28