

**Nix Brand  
Fiberglass Sucker Rod**

Fiberglass Sucker Rod will not rust, rot splinter, absorb water, freeze, conduct electricity, corrode, or remain bent through rough handling. Each rod comes with two rod guides.



NIX Fiberglass Sucker Rod				
Product Number	Thread Size (in)	Rod Diameter (in)	Rod Length (ft)	Approx. Weight (lbs/100')
58FSR	5/8	5/8	21	31
34FSR	7/8	3/4	21	53

Fiberglass Sucker Rod Coupling Repair Kits				
Product Number	Connection	Thread Size (in)	Rod Size (in)	Approx. Weight (lbs)
MRK58FSR	Male	5/8	5/8	2
MRK58FSR	Female	5/8	5/8	2
MRK34FSR	Male	7/8	7/8	3
FRK34FSR	Female	7/8	7/8	3



**Nix Brand  
Wood Sucker Rod**

Wood sucker rods come in random lengths and are priced by the foot. Rods can be cut and riveted for required sizing.

Wood Sucker Rod			
Product Number	Rod Diameter (in)	Thread Size (in)	Approx. Weight (lbs/100')
WSR118	1-1/8"	5/8"	50
WSR138	1-3/8"	7/8"	80
WSR158	1-5/8"	7/8"	120

Wood Rod Repair Couplings				
Product Number	Rod Size (in)	Thread Size (in)	Connection	Approx. Weight (lbs)
WRCF58	1-1/8	5/8	Female	2
WRCM58			Male	2
WRCF78	1-3/8 or 1-5/8	7/8	Female	4
WRCM78			Male	3

Copper Repair Rivets		
Product Number	Rivet Size (in)	Rod Size (in)
CR316	3/16 X 1-5/8	1-1/8
CR14	1/4 X 2	1-3/8 & 1-5/8
CR516	5/16 X 2-3/8	1-7/8

**Sinker Bars**

Solid Steel or 304 Stainless Steel sinker bars should be installed above plunger valves to prevent rod bow and improve pumping efficiency.

Sinker Bars					
Product Number	Rod Material	Thread Size Male (in)	Rod Diameter (in)	Rod Length (in)	Approx. Weight (lbs)
SB58	Steel	5/8	1-1/4	36	12
SB78	Steel	7/8	1-1/4	36	12
SSB58	304 SS	5/8	1-1/4	36	12
SSB78	304 SS	7/8	1-1/4	36	12