

**Schedule 80 Threaded Drop Pipe**

- Schedule 80, white PVC pipe, male threads, both ends.
- Manufactured from 1120 1220 PVC - bears the NSF Seal of Certification.
- The smooth interior improves flow characteristics, cuts friction loss.
- Light weight, approximately one fourth the weight of schedule 40 iron pipe.
- Easy to install, furnished in 20' lengths with thread protectors on each end.
- Not subject to rust, corrosion, or electrolytic deterioration.



PVC Schedule 80 Threaded Drop Pipe							
Product Number	IPS Size (in)	Approx. Weight (lbs./100')	Max. Pres. (PSI)	Max. Depth 60 PSI (ft)	Max. Pump (HP)	Max. Flow (GPM)	Lift Qty. (ft)
DP010	1	42	320	600	1.5	10	2500
DP012	1-1/4	58	360	460	2	20	2000
DP015	1-1/2	70	240	400	5	25	1000
DP020	2	97	200	360	7.5	45	1000

**Schedule 120 Heavy Duty Threaded Drop Pipe**

- Schedule 120, white PVC pipe, male threads, both ends.
- Manufactured to the same specifications as above using Schedule 120 PVC.



PVC Schedule 120 Threaded Drop Pipe							
Product Number	IPS Size (in)	Approx. Weight (lbs./100')	Max. Pres. (PSI)	Max. Depth 60 PSI (ft)	Max. Pump (HP)	Max. Flow (GPM)	Lift Qty. (ft)
HDP010	1	46	360	680	1.5	10	2500
HDP012	1-1/4	64	300	550	2	20	2000
HDP015	1-1/2	78	270	480	5	25	1000
HDP020	2	110	240	460	7.5	45	1000

Depth settings are reprinted from the manufacturer's specification data and are subject to many variables of the individual application. Depth ratings assume that the pump and motor is 200 lbs or less, temperature is 73.4°F and that the discharge pressure is 60 PSI or less. In addition the drop pipe must be full of water to avoid water hammer. Burdick & Burdick, Inc. will assume no responsibility and makes no warranties or guaranties regarding drop pipe failure.